

Remote sensing and GIS based landslide hazard mapping at Cameron Highland, Malaysia using frequency ratio and logistic regression models

B. Pradhan (1) and S. Lee (2)

(1) Cilix Corporation, #1 - 5 & 1-6, Innovation House, Technology Park Malaysia, Bukit Jalil Highway, Bukit Jalil, 57000, Kuala Lumpur, Malaysia (biswajeet@mailcity.com / Fax: +603-89417964 / Phone: +60-123126773) (2) Geoscience Information Center, Korea Institute of Geoscience and Mineral Resources (KIGAM), 30, Kajung-Dong, Yusung-Gu, Taejon, Korea (leesaro@kigam.re.kr / Fax: +82-42-861-9714 / Phone: +82-42-868-3057)

The aim of this study is to evaluate the landslide hazards at Cameron area, Malaysia, using a Geographic Information System (GIS) and remote sensing. Landslide locations were identified in the study area from interpretation of aerial photographs and from field surveys. Topographical and geological data and satellite images were collected, processed, and constructed into a spatial database using GIS and image processing. The factors chosen that influence landslide occurrence were: topographic slope, topographic aspect, topographic curvature and distance from drainage, all from the topographic database; lithology and distance from lineament, taken from the geologic database; land cover from TM satellite image; the vegetation index value from Landsat satellite images; and precipitation distribution from meteorological data. Landslide hazardous area were analyzed and mapped using the landslide-occurrence factors by frequency ratio and logistic regression models. The results of the analysis were verified using the landslide location data and compared with probability model. The validation results showed that the frequency ratio model (accuracy is 89.25%) is better in prediction than logistic regression (accuracy is 85.73%) model.