Geophysical Research Abstracts, Vol. 8, 04640, 2006 SRef-ID: 1607-7962/gra/EGU06-A-04640 © European Geosciences Union 2006



Mapping potential evapotranspiration using high resolution digital terrain models, geographical information systems and regression-based techniques: application in the Ebro valley (NE-Spain)

S. Lanjeri (1), J. M. Cuadrat (1), S. M. Vicente-Serrano (2), M. A. García-Vera (3) (1) Departamento de Geografía. Universidad de Zaragoza. C/ Pedro Cerbuna 12. 50009. Zaragoza. Spain, (2) Instituto Pirenaico de Ecología, CSIC (Spanish Research Cuncil), Campus de Aula Dei, P.O. Box 202, Zaragoza 50080, Spain, (3) Oficina de Planificación Hidrológica, Confederación Hidrográfica del Ebro. Paseo de Sagasta 24-26. 50071 Zaragoza, Spain.

Monthly and annual potential evapotranspiration (PET) was obtained in a continuous way with a resolution of 100 meters by means of the combined use of meteorological data, high resolution digital terrain models, Geographical Information Systems (GIS) and regression-based techniques. The analysis was done in the Ebro valley, a very complex topographic area, in which the climatology has diverse spatial patterns. The PET was calculated following the Hargreave's method, which only requires information on maximum and minimum temperature, a parameter widely recorded in the weather stations. The PET calculation was done using continuous temperature maps obtained at a resolution of 100 meters by means of GIS and regression-based interpolation. Also a local interpolation of the residuals obtained from the regression models was performed to improve the results. The interpolation was carried out from a dense spatial data base composed by 311 temperature stations. Interpolations were done by means of the 80% of the records (248 temperature stations). The quality of the PET maps was tested by means of the remaining 20% temperature stations, in which PET was calculated locally also using the Hargreave's method. The Willomott's D statistic was used to compare between the local PET estimations and those results obtained from the continuous models. The results indicate a high reliability. Also the PET maps were tested by means of independent PET calculations obtained in some agroclimatological stations by means of the reference PET method of Penmann-Montheith. The

PET maps obtained in this paper may be very useful for water resources, irrigation and environmental management.