

Exploring high-resolution operational weather forecasts for flash-flood prediction

J. Thielen (1), S. Anquetin (2) and J. Younis (1)

(1) Institute for Environment and Sustainability, European Commission Joint Research Centre, Ispra Italy (jutta.thielen@jrc.it, jalal.younis@jrc.it), (2) Laboratoire d'études des Transferts en Hydrologie et Environnement (LTHE), Grenoble, France (sandrine.anquetin@hmg.inpg.fr)

1. INTRODUCTION

In Mediterranean Europe, flash flooding is one of the most devastating hazards in terms of human life loss and infrastructures. Over the last two decades, flash floods brought losses of a billion Euros of damage in France alone. The objective of this study is to investigate if operationally available short-range numerical weather forecasts together with a rainfall-runoff model can be used as early indication for the occurrence of flash floods.

The study is focussed on the Cévennes-Vivarais region, Southeast of the Massif Central, France, which is often prone to flash flood. The main objective aims at evaluating the hydrometeorological chain for the forecasting of one of the main flash flood event that took place in this region in September 2002 (Delrieu et al., 2005). During the 8 and 9 September, more than 700 mm were recorded; the flash flood took 24 lives and the economical damages were evaluated at 1.2 billions euros (Huet et al., 2003).

The short range weather forecasts are derived from the Lokalmmodell of the Deutscher Wetterdienst, the German national weather service, and is available twice a day, at 00:00 and at 12:00 on a grid spacing of 7 km and an hourly temporal resolution. The outputs are driving the hydrological rainfall-runoff model LISFLOOD (van der Knijff, 2007, de Roo et al., 2000). It is set-up for the whole study area comprising several smaller river basins on a grid spacing of 1 km and runs with an hourly time step for the flood predictions.

One of the challenges in flash flood forecasting is that the watersheds are typically small and good observational networks of both rainfall and discharge are rare. Therefore, hydrological models are difficult to calibrate and the simulated river discharges cannot always be compared with ground truth. The miss of observation in most flash flood prone basins, therefore, leads to develop a method where the excess of the simulated discharge above a critical threshold can provide the forecast. A model consistent approach is then proposed based on the evaluation of discharge threshold values obtained with the simulation of long-time series. Then, the forecasted discharges, for a given event, are compared against these thresholds, available at every pixel. The major advantage of this approach is that any systematic over- or under-prediction of the

model is compensated for. If the model tends to overestimate discharges in a given river reach, either because of a non-optimised parameterization or lack of processes such irrigation or reservoir operations, this would be reflected in the thresholds as well as in the forecasts.

2. RESULTS AND CONCLUSIONS

For this study, the long time series simulations are based on observed daily meteorological data derived from observed meteorological stations for the time period 1990-2003. From the daily hydrological simulations critical thresholds have been derived as well as the starting conditions for the flood forecasts. The flood forecasts were driven by the 48h DWD weather forecasts starting on 20020906 00:00 and then in 12h intervals the next weather forecasts until 20020910 12:00 o'clock forecast. The initial conditions were always taken from the 00:00 forecasts. Both the 00:00 and 12:00 forecasts from the same day start with the same initial conditions.

From the obtained results, it appears that the forecast from the 7th at 12:00 exceeds in fact the severe and high flood thresholds, indicating a possibility for a severe flood within the coming 2 days. This time is required for the civil protection to organize the warning of the territory and to prepare the eventual rescues. The later forecasts confirm the severity of the flood. Moreover, the simulated flood alert highlights the severity of the event at the regional scale and in particularly, the area around the Gard and Virdourle is at particular risk.

3. REFERENCES

De Roo, A., Wesseling, C. G. & Van Deursen, W. P. A. (2000). Physically based river basin modelling within a GIS: the LISFLOOD model. *Hydrological Processes*, Vol. 4, Issues 11-12, p.1981-1992. Delrieu G., V. Ducrocq, E. Gaume, J. Nicol, O. Payrastre, E. Yates, P.E. Kirstetter, H. Andrieu, P.-A. Aral, C. Bouvier, J.-D. Creutin, M. Livet, S. Anquetin, M. Lang, L. Neppel, C. Obled, J. Parent-du-Châtelet, G.-M. Saulnier, A. Walpersdorf and W. Wobrock, 2005, The catastrophic flash-flood event of 8-9 September 2002 in the Gard region, France: a first case study for the Cévennes-Vivarais Mediterranean Hydro-meteorological Observatory, *J. Hydrometeorology*, 6, 34-52. Huet P., X. Martin, J.-L. Prime, P. Foin, C. Laurain and P. Canard, 2003, Retour d'expérience des crues de septembre 2002 dans les départements du Gard, de l'Hérault, du Vaucluse, des Bouches-du-Rhône, de l'Ardèche et de la Drôme. Technical report, Ministère de l'Ecologie et du Développement Durable, République Française, 133pp. Van Der Knijff, J. & A. De Roo (2005). LISFLOOD - distributed water balance and flood simulation model. User manual (version December 2005). European Report in press, 80p.